



Harlequin Liberty[®] LatchLoc




Harlequin Liberty® LatchLoc is a modular, sprung floor panel system manufactured from layered birch plywood featuring dual density elastomer blocks on the underside to give uniform and consistent shock damping. The panels are laid in a brickwork fashion onto the subfloor, so that cross-joins do not coincide. The panels join together by a rounded tongue and groove, which is secured in place using our 'one turn of the key' latch and lock mechanism.

Harlequin Liberty LatchLoc panels are finished by choosing an appropriate Harlequin vinyl performance floor. Installation of the panels and the accompanying vinyl can be carried out by the customer or by the Harlequin Contracts Team. Solid kerbs and ramps are available for stage use or where the sprung floor does not extend to the walls of the studio.


Harlequin Liberty LatchLoc sprung floor panels are available as stage panels for touring. These panels have tempered hardboard attached to the underside for ease of sliding the panels into position to protect the elastomer blocks. The panels and accompanying portable Harlequin vinyl floor can also be stored on carts, providing an easy and safe way for stage crews to move them on tour and around a venue.

Liberty LatchLoc Stage Panels





Harlequin's 'latch and lock' system



American Harlequin Corporation 1531 Glen Avenue Moorestown, NJ 08057

(800) 642 6440 contact@harlequinfloors.com harlequinfloors.com

The Company reserves the right to make any variation in design or construction of the material described. © Harlequin Floors 08/2022. PHILADELPHIA FORT WORTH LOS ANGELES LAS VEGAS LONDON PARIS BERLIN LUXEMBOURG MADRID SYDNEY HONG KONG

TOKYO

Specification Guide

Installation	Portable/Modular					
Full Size Panel	96" x 48"					
Half Size Panel	48" x 48"					
Weight	86 lbs (Full Size) 43 lbs (Half Size)					
Thickness	11/2"					
	15⁄/8" (Stage)					
Testing Standards	DIN 18032-2					
Average Shock Absorption	67%					
Vertical Deformation	4.1mm					
Area Deflection	12.8%					
Rolling Load	>1500 N					
Maximum Point Load	2482 lbs					

Harlequin Sprung Floor Application Guide

Along with Harlequin Liberty LatchLoc, we offer additional sprung flooring options, which are listed below along with the recommended surface. These recommendations are based on experience and customer preference only. Please contact a Flooring Specialist to determine which option best suits your requirements.

✓ = We recommend.	Allegro	Cascade	Fiesta	FreeStyle	Hardwood	Hi-Shine	Marine	Reversible	Reversible Pro	Standfast	Studio	Studio B
	⊲	0	ш	ш	1	1	2	a	Œ	S	S	<i>C</i>)
Activity		1	1	1	1		1			1	\checkmark	1
AeroDeck		1	1	1		1		1	1	1	\checkmark	1
Flexity		1	1	1	1	1	1	1	1	1	1	1
Liberty HD		1	1	1		\checkmark	\checkmark	1	1	1	\checkmark	1
Liberty LatchLoc		1	1	1		1	1	1	1	1	1	1
WoodSpring		1	1	1	1		1			1	1	1

CALL 800-642-6440 or VISIT www.harlequinfloors.com

For samples or information on Harlequin Floors complete range of vinyl and sprung floors.