



Liberty LatchLoc Stage Panels









## American Harlequin Corporation 1531 Glen Avenue Moorestown, NJ 08057

(800) 642 6440 contact@harlequinfloors.com harlequinfloors.com

The Company reserves the right to make any variation in design or construction of the material described. © Harlequin Floors 1/2024 LOS ANGELES LAS VEGAS LONDON PARIS BERLIN LUXEMBOURG MADRID SYDNEY HONG KONG TOKYO

PHILADELPHIA

## Harlequin Liberty<sup>®</sup> LatchLoc



Harlequin Liberty® LatchLoc is a modular, sprung floor panel system, manufactured from engineered board with dual-density elastomer blocks on the underside to give uniform and consistent shock damping. The panels are laid in a brickwork fashion onto the sub-floor, so that cross joins do not coinside. They are linked to each other by a hardwood dowel, which is secured into place using our 'one turn of the key' latch and lock mechanism. Solid curbs and ramps are available for stage and studio wall extensions. Harlequin Liberty LatchLoc stage panels have tempered hardboards for sliding and protecting elastomer blocks. Storage on carts offers ease and safety for stage crews during tours and venue setup.

**Performance Surface:** Harlequin Liberty LatchLoc is finished by choosing an appropriate Harlequin vinyl performance surface.

**Installation:** Harlequin Liberty LatchLoc sprung floor panels are quick and easy to install. The panels and accompanying portable Harlequin viny performance surface can also be stored on carts, providing an easy and safe way for crews to move them while on tour or around a venue.

## **Specification Guide**

Installation	Portable / Modular					
Floor panel size	Full 96" x 48", Half 48" x 48"					
Overall thickness	1¹/2″ nominal (without vinyl performance surface) 1⁵⁄₃″ nominal (with vinyl performance surface)					
Weight	92 lb full size, 46 lb half size Stage 94 lb full size, 47 lb half size					
Testing standards	DIN 18032-2					
Average shock absorption	67%					
Uniform distribution Load	>2248 lb					
Point load	>809 lb					
Rolling load	>1500 N					
Vertical deformation	4.1mm					
Area deflection	12.8%					
Fire rating	Bfls 1 to EN 13501					

## Harlequin Sprung Floor Application Guide

Along with Harlequin Activity, we offer additional sprung flooring options, which are listed below along with the recommended surface. These recommendations are based on experience and customer preference only. Please contact a Flooring Specialist to determine which option best suits your requirements.

Pro

le le

I = We recommend.

	Allegro	Cascade	Fiesta	FreeStyl	Hardwo	Hi-Shine	Marine	Reversik	Reversik	Standfa	Studio	Studio F
Activity		1	1	1	1		1			1	1	-
AeroDeck		1	1	1		1		1	1	1	1	
Flexity		1	1	1	1	1	1	1	1	1	1	
Liberty HD		1	1	1		1	1	1	1	1	1	
Liberty LatchLoc		1	1	1		1	1	1	1	1	1	
WoodSpring		1	1	1	1		1			1	1	

CALL 800-642-6440 or VISIT www.harlequinfloors.com

For samples or information on Harlequin Floors complete range of vinyl and sprung floors.